



Upholstery & carpet cleaner aerosol

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Issue date:20/08/2020

Revision date: 22/08/2022

Supersedes: 22/01/2020

Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Trade name : Upholstery & carpet cleaner aerosol
Type of product : Cleaning agent
Product code : SH819
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Supplier's details

Manufacturer

Shield Chemicals (Pty) Ltd
9 London Rd
Apex
P.O. Box 1939
1501 Benoni - South Africa
T (011) 421 7111
info@shieldchem.co.za

1.4. Emergency telephone number

Emergency number : (011) 421 7111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Aerosol, Category 1 H222;H229
Hazardous to the aquatic environment — Acute Hazard, Category 3 H402
Full text of H statements : see section 16

2.2. Label elements

Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA) :



GHS02

Signal word (GHS-ZA) : Danger
Hazardous ingredients : propane; butane, liquefied, under pressure; Sodium dodecyl sulphate; SAS
Hazard statements (GHS-ZA) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H402 - Harmful to aquatic life
Precautionary statements (GHS-ZA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P273 - Avoid release to the environment.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Pressurised container: May burst if heated,Extremely flammable aerosol,Harmful to aquatic life

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
butane, liquefied, under pressure	(CAS-No.) 106-97-8	5.0 - 10.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401

Upholstery & carpet cleaner aerosol

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Name	Product identifier	%	Classification according to the United Nations GHS
propane	(CAS-No.) 74-98-6	1.0 - 5.0	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified
SAS	(CAS-No.) 97489-15-1	1.0 - 5.0	Acute Tox. 4 (Oral), H302 Aquatic Acute 2, H401
Sodium dodecyl sulphate	(CAS-No.) 151-21-3	1.0 - 5.0	Acute Tox. 5 (Dermal), H313 Aquatic Acute 3, H402 Aquatic Chronic Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Upholstery & carpet cleaner aerosol

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

propane (74-98-6)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Propane
OEL TWA (mg/m ³)	1800 mg/m ³
OEL TWA (ppm)	1000 ppm
Regulatory reference	Government Notice No. R 904
butane, liquefied, under pressure (106-97-8)	
South Africa - Occupational Exposure Limits (Recommended Limits)	
Local name	Butane
OEL TWA (mg/m ³)	1430 mg/m ³
OEL TWA (ppm)	600 ppm
OEL STEL (mg/m ³)	1780 mg/m ³
OEL STEL (ppm)	750 ppm
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	n-Butane
OEL TWA (mg/m ³)	1430 mg/m ³
OEL TWA (ppm)	600 ppm
OEL STEL (mg/m ³)	1780 mg/m ³
OEL STEL (ppm)	750 ppm
Regulatory reference	Government Notice No. R 904

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : Off-white.
Odour : characteristic.
Odour threshold : No data available
pH : 6 - 7
pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Extremely flammable aerosol.
Vapour pressure : No data available
Vapour pressure at 50 °C : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available
Relative density of saturated gas/air mixture : No data available

Upholstery & carpet cleaner aerosol

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosive limit (LEL)	: No data available
Upper explosive limit (UEL)	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

propane (74-98-6)	
LC50 inhalation rat (ppm)	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
butane, liquefied, under pressure (106-97-8)	
LC50 inhalation rat (mg/l)	1442.738 - 1443 mg/l 15 MIN
LC50 inhalation rat (ppm)	800000 ppm 15 MIN
SAS (97489-15-1)	
LD50 oral rat	500 - 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Sodium dodecyl sulphate (151-21-3)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation	: Not classified pH: 6 - 7
Serious eye damage/irritation	: Not classified pH: 6 - 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Upholstery & carpet cleaner aerosol

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Upholstery & carpet cleaner aerosol	
Vaporizer	Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

propane (74-98-6)	
LC50 fish 1	24 mg/l (96 h, Pisces, Literature study)
LC50 fish 2	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 Daphnia 1	7 mg/l (48 h, Daphnia magna, Literature study)
BCF fish 1	9 - 25 (Pisces, QSAR)
Log Pow	1.09 - 2.8 (Experimental value, 20 °C)

butane, liquefied, under pressure (106-97-8)	
LC50 fish 1	> 1000 mg/l (96 h, Pimephales promelas, QSAR)
EC50 72h algae (1)	5.3 - 5.5 mg/l (Algae, QSAR)
Log Pow	2.89 (Experimental value)

SAS (97489-15-1)	
LC50 fish 1	5.5 mg/l Test organisms (species): Leuciscus idus melanotus
LC50 fish 2	8.4 mg/l Test organisms (species): Leuciscus idus melanotus
EC50 Daphnia 1	9.2 mg/l Test organisms (species): Daphnia magna
EC50 Daphnia 2	9.8 mg/l Test organisms (species): Daphnia magna
EC50 72h algae (1)	> 61 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h algae (2)	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	1.6 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

Sodium dodecyl sulphate (151-21-3)	
LC50 fish 1	29 mg/l Test organisms (species): Pimephales promelas
EC50 other aquatic organisms 1	11.1 mg/l Test organisms (species): other aquatic crustacea:Pseudosida ramosa
EC50 72h algae (1)	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h algae (2)	53 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC chronic fish	>= 1.357 mg/l Test organisms (species): Pimephales promelas Duration: '42 d'

12.2. Persistence and degradability

Upholstery & carpet cleaner aerosol	
Persistence and degradability	No additional information available

propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.

butane, liquefied, under pressure (106-97-8)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

Upholstery & carpet cleaner aerosol	
Bioaccumulative potential	No additional information available

propane (74-98-6)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

butane, liquefied, under pressure (106-97-8)	
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Upholstery & carpet cleaner aerosol	
Mobility in soil	No additional information available

Upholstery & carpet cleaner aerosol

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

propane (74-98-6)	
Surface tension	0.016 N/m (-47 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).

butane, liquefied, under pressure (106-97-8)	
Surface tension	< 0.1 N/m (0 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available




SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		 Not applicable
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

- SANS

Special provisions (SANS)	: 63, 190
Limited quantities (SANS)	: See SP277
Limited quantities (SANS)	: See SP277
Packagings, large packagings and IBCs	: P003
Packing instructions (SANS)	
Packagings, large packagings and IBCs Special packing instructions (SANS)	: PP17, PP87

- IMDG

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None

- IATA

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG

Upholstery & carpet cleaner aerosol

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

Issue date	: 20/08/2020
Revision date	: 22/08/2022
Supersedes	: 22/01/2020

Full text of H-statements:

H220	Extremely flammable gas.
H227	Combustible liquid
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

SDS South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.