



# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Date of issue:04/02/2020

Revision date:

Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : Sheen Natural Vinyl, Plastic & Rubber Care - Cherry  
 Type of product : Vehicle Interior Aerosol Dashboard Spray Cleaner  
 Product code : SH303  
 Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cleans and restores vinyl, plastic and rubber

#### 1.3. Supplier's details

##### Manufacturer

Shield Chemicals (Pty) Ltd  
 9 London Rd  
 Apex  
 P.O. Box 1939  
 1501 Benoni - South Africa  
 T (011) 421 7111  
[info@shieldchem.co.za](mailto:info@shieldchem.co.za)

#### 1.4. Emergency telephone number

Emergency number : (011) 421 7111

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to the United Nations GHS

Aerosol, Category 1	H222;H229
Acute toxicity (dermal), Category 5	H313
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Acute Hazard, Category 2	H401
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H statements : see section 16

#### 2.2. Label elements

##### Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA) :



Signal word (GHS-ZA) :

Danger

Hazard statements (GHS-ZA) :

H222 - Extremely flammable aerosol.  
 H229 - Pressurised container: May burst if heated.  
 H313 - May be harmful in contact with skin  
 H315 - Causes skin irritation.  
 H336 - May cause drowsiness or dizziness.  
 H373 - May cause damage to organs through prolonged or repeated exposure.  
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS-ZA) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 - Do not spray on an open flame or other ignition source.  
 P251 - Do not pierce or burn, even after use.  
 P260 - Do not breathe mist, vapours.  
 P261 - Avoid breathing mist, vapours.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P273 - Avoid release to the environment.  
 P280 - Wear eye protection, protective clothing, protective gloves.

# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

P302+P352 - IF ON SKIN: Wash with plenty of water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 - Call a doctor if you feel unwell.  
P314 - Get medical advice if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label)  
P332+P313 - If skin irritation occurs: Get medical advice.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 - Dispose of contents and container to an approved waste disposal plant.

### 2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour, May cause damage to organs through prolonged or repeated exposure, May cause drowsiness or dizziness, Harmful in contact with skin, Causes skin irritation, Toxic to aquatic life, Toxic to aquatic life with long lasting effects.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
hexane	(CAS-No.) 110-54-3	21.312 - 42.624	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butane, liquefied, under pressure	(CAS-No.) 106-97-8	20 - 30	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401
heptane	(CAS-No.) 142-82-5	10 - 20	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
propane	(CAS-No.) 74-98-6	10 - 20	Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified
n-pentane	(CAS-No.) 109-66-0	5 - 10	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : Irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe mist, vapours. Avoid contact with skin, eyes and clothing.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe mist, vapours. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

hexane (110-54-3)	
South Africa - Occupational Exposure Limits (Recommended Limits)	
Local name	n-Hexane
OEL TWA (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
OEL TWA (ppm)	20 ppm
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	n-Hexane
OEL TWA (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
OEL TWA (ppm)	20 ppm
Regulatory reference	Government Notice No. R 904
butane, liquefied, under pressure (106-97-8)	
South Africa - Occupational Exposure Limits (Recommended Limits)	
Local name	Butane
OEL TWA (mg/m <sup>3</sup> )	1430 mg/m <sup>3</sup>
OEL TWA (ppm)	600 ppm
OEL STEL (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
OEL STEL (ppm)	750 ppm
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	n-Butane

# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

<b>butane, liquefied, under pressure (106-97-8)</b>	
OEL TWA (mg/m <sup>3</sup> )	1430 mg/m <sup>3</sup>
OEL TWA (ppm)	600 ppm
OEL STEL (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
OEL STEL (ppm)	750 ppm
Regulatory reference	Government Notice No. R 904
<b>propane (74-98-6)</b>	
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Propane
OEL TWA (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OEL TWA (ppm)	1000 ppm
Regulatory reference	Government Notice No. R 904

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Colour : clear.  
Odour : Cherry.  
Odour threshold : No data available  
pH : No data available  
pH solution : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Relative evaporation rate (ether=1) : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : Not applicable  
Vapour pressure : No data available  
Vapour pressure at 50 °C : No data available  
Relative vapour density at 20 °C : No data available  
Relative density : No data available  
Relative density of saturated gas/air mixture : No data available  
Density : No data available  
Relative gas density : No data available  
Solubility : No data available  
Log Pow : No data available  
Log Kow : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosive properties : No data available

# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosive limit (LEL)	: No data available
Upper explosive limit (UEL)	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: May be harmful in contact with skin.
Acute toxicity (inhalation)	: Not classified

ATE ZA (dermal)	3933.787 mg/kg bodyweight
<b>hexane (110-54-3)</b>	
LD50 oral rat	16000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 3350 mg/kg bodyweight (Equivalent or similar to OECD 402, 4 h, Rabbit, Male, Read-across, Dermal)
LC50 inhalation rat (ppm)	> 5000 ppm (Equivalent or similar to OECD 403, 24 h, Rat, Male, Experimental value, Inhalation (vapours))
<b>heptane (142-82-5)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal)
LC50 inhalation rat (mg/l)	> 29.29 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
<b>n-pentane (109-66-0)</b>	
LD50 oral rat	> 2000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 20 mg/l air (4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
<b>butane, liquefied, under pressure (106-97-8)</b>	
LC50 inhalation rat (mg/l)	1442.738 - 1443 mg/l 15 MIN
LC50 inhalation rat (ppm)	800000 ppm 15 MIN
<b>propane (74-98-6)</b>	
LC50 inhalation rat (ppm)	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.  
Aspiration hazard : Not classified

<b>Sheen Natural Vinyl, Plastic &amp; Rubber Care - Cherry</b>	
Vaporizer	Aerosol

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.  
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

<b>hexane (110-54-3)</b>	
BCF fish 1	501.187 (Other, Pimephales promelas, QSAR)
Log Pow	4 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Log Koc	3.34 (log Koc, QSAR)

<b>heptane (142-82-5)</b>	
BCF other aquatic organisms 1	552 (BCFBAF v3.00, Calculated value)
Log Pow	4.66 (Experimental value)
Log Koc	2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

<b>n-pentane (109-66-0)</b>	
LC50 fish 1	4.26 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	2.7 mg/l (Other, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
ErC50 (algae)	10.7 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Scenedesmus sp., Static system, Fresh water, Experimental value, GLP)
BCF fish 1	171 (Pimephales promelas, QSAR)
Log Pow	3.45 (Experimental value, Other, 25 °C)
Log Koc	2.9 (log Koc, QSAR)

<b>butane, liquefied, under pressure (106-97-8)</b>	
LC50 fish 1	> 1000 mg/l (96 h, Pimephales promelas, QSAR)
EC50 72h algae (1)	5.3 - 5.5 mg/l (Algae, QSAR)
Log Pow	2.89 (Experimental value)

<b>propane (74-98-6)</b>	
LC50 fish 1	24 mg/l (96 h, Pisces, Literature study)
LC50 fish 2	49.9 mg/l (96 h, Pisces, Fresh water, QSAR)
EC50 Daphnia 1	7 mg/l (48 h, Daphnia magna, Literature study)
BCF fish 1	9 - 25 (Pisces, QSAR)
Log Pow	1.09 - 2.8 (Experimental value, 20 °C)

#### 12.2. Persistence and degradability

<b>Sheen Natural Vinyl, Plastic &amp; Rubber Care - Cherry</b>	
Persistence and degradability	No additional information available

<b>hexane (110-54-3)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
ThOD	3.52 g O <sub>2</sub> /g substance

<b>heptane (142-82-5)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.92 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.06 g O <sub>2</sub> /g substance
ThOD	3.52 g O <sub>2</sub> /g substance
BOD (% of ThOD)	> 0.5 (5 day(s), Literature study)

<b>n-pentane (109-66-0)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>butane, liquefied, under pressure (106-97-8)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable in water.

# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

### 12.3. Bioaccumulative potential

Sheen Natural Vinyl, Plastic & Rubber Care - Cherry	
Bioaccumulative potential	No additional information available
<b>hexane (110-54-3)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Potential for bioaccumulation ( $500 \leq \text{BCF} \leq 5000$ ).
<b>heptane (142-82-5)</b>	
BCF other aquatic organisms 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Potential for bioaccumulation ( $4 \geq \text{Log Kow} \leq 5$ ).
<b>n-pentane (109-66-0)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation ( $\text{Log Kow} < 4$ ).
<b>butane, liquefied, under pressure (106-97-8)</b>	
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation ( $\text{Log Kow} < 4$ ).
<b>propane (74-98-6)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation ( $\text{Log Kow} < 4$ ).
<b>12.4. Mobility in soil</b>	
Sheen Natural Vinyl, Plastic & Rubber Care - Cherry	
Mobility in soil	No additional information available
<b>hexane (110-54-3)</b>	
Surface tension	0.018 N/m (25 °C, 1 g/l)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for mobility in soil.
<b>heptane (142-82-5)</b>	
Surface tension	19.66 mN/m (25 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.
<b>n-pentane (109-66-0)</b>	
Surface tension	0.013 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.
<b>butane, liquefied, under pressure (106-97-8)</b>	
Surface tension	< 0.1 N/m (0 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).
<b>propane (74-98-6)</b>	
Surface tension	0.016 N/m (-47 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Not applicable (gas).

### 12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010




### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 Additional information : Flammable vapours may accumulate in the container.

### SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
<b>14.1. UN number</b>		
1950	1950	1950
<b>14.2. Proper Shipping Name</b>		
AEROSOLS	AEROSOLS	Aerosols, flammable
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		 Not applicable
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : Yes	Dangerous for the environment : No :	Dangerous for the environment : No
No supplementary information available		

#### 14.6. Special precautions for user

##### - SANS

Special provisions (SANS) : 63, 190  
 Limited quantities (SANS) : See SP277  
 Limited quantities (SANS) : See SP277  
 Packagings, large packagings and IBCs : P003  
 Packing instructions (SANS)  
 Packagings, large packagings and IBCs Special : PP17, PP87  
 packing instructions (SANS)

##### - IMDG

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
 Packing instructions (IMDG) : P207, LP200  
 Special packing provisions (IMDG) : PP87, L2  
 EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
 EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
 Stowage category (IMDG) : None

##### - IATA

PCA Excepted quantities (IATA) : E0  
 PCA Limited quantities (IATA) : Y203  
 PCA limited quantity max net quantity (IATA) : 30kgG  
 PCA packing instructions (IATA) : 203  
 PCA max net quantity (IATA) : 75kg  
 CAO packing instructions (IATA) : 203  
 CAO max net quantity (IATA) : 150kg  
 Special provisions (IATA) : A145, A167, A802  
 ERG code (IATA) : 10L

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable



# Sheen Natural Vinyl, Plastic & Rubber Care - Cherry

## Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

### SECTION 15: Regulatory information

#### 15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

### SECTION 16: Other information

Date of issue : 04/02/2020

Full text of H-statements:

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

SDS South Africa

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*