



Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Date of issue:05/02/2020

Revision date:

Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Trade name : Sheen vinyl, plastic & rubber care - Island Coconut
Type of product : Vehicle Interior Aerosol Dashboard Spray Cleaner
Product code : SH240, SH728
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cleans and restores vinyl, plastic and rubber

1.3. Supplier's details

Manufacturer

Shield Chemicals (Pty) Ltd
9 London Rd
Apex
P.O. Box 1939
1501 Benoni - South Africa
T (011) 421 7111
info@shieldchem.co.za

1.4. Emergency telephone number

Emergency number : (011) 421 7111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

| | |
|---|-----------|
| Aerosol, Category 1 | H222;H229 |
| Acute toxicity (dermal), Category 5 | H313 |
| Skin corrosion/irritation, Category 2 | H315 |
| Skin sensitisation, Category 1 | H317 |
| Reproductive toxicity, Additional category, Effects on or via lactation | H362 |
| Specific target organ toxicity — Single exposure, Category 3, Narcosis | H336 |
| Specific target organ toxicity — Repeated exposure, Category 2 | H373 |
| Hazardous to the aquatic environment — Acute Hazard, Category 2 | H401 |
| Hazardous to the aquatic environment — Chronic Hazard, Category 2 | H411 |

Full text of H statements : see section 16

2.2. Label elements

Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA) :



GHS02

GHS07

GHS08

GHS09

Signal word (GHS-ZA) : Danger

Hazardous ingredients : hexane; heptane; n-pentane; Silicone; C11-C15 Isoalkanes; p-methoxybenzyl acetate

Hazard statements (GHS-ZA) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H313 - May be harmful in contact with skin
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H362 - May cause harm to breast-fed children.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS-ZA) : P201 - Obtain special instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.

Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

P251 - Do not pierce or burn, even after use.
P260 - Do not breathe mist, vapours.
P261 - Avoid breathing mist, vapours.
P263 - Avoid contact during pregnancy and while nursing.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - IF exposed or concerned: Get medical advice.
P312 - Call a doctor if you feel unwell.
P314 - Get medical advice if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label)
P332+P313 - If skin irritation occurs: Get medical advice.
P333+P313 - If skin irritation or rash occurs: Get medical advice.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Pressurised container: May burst if heated, Extremely flammable aerosol, May cause harm to breast-fed children, May cause damage to organs through prolonged or repeated exposure, May cause drowsiness or dizziness, Harmful in contact with skin, Causes skin irritation, May cause an allergic skin reaction, Toxic to aquatic life, Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to the United Nations GHS |
|-----------------------------------|--------------------|-------------|--|
| hexane | (CAS-No.) 110-54-3 | 21.0 - 45.0 | Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |
| butane, liquefied, under pressure | (CAS-No.) 106-97-8 | 20.0 - 30.0 | Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute 2, H401 |
| heptane | (CAS-No.) 142-82-5 | 10.0 - 15.0 | Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| propane | (CAS-No.) 74-98-6 | 10.0 - 20.0 | Pyr. Gas Not classified Flam. Gas 1, H220 Aquatic Acute Not classified |
| n-pentane | (CAS-No.) 109-66-0 | 5.0 - 10.0 | Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 |

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe mist, vapours. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Avoid contact during pregnancy/while nursing. Do not breathe mist, vapours. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| hexane (110-54-3) | |
|---|----------------------------|
| South Africa - Occupational Exposure Limits (Recommended Limits) | |
| Local name | n-Hexane |
| OEL TWA (mg/m ³) | 70 mg/m ³ |
| OEL TWA (ppm) | 20 ppm |
| Regulatory reference | Government Notice. R: 1179 |
| South Africa - Occupational Exposure Limits (Airborne Pollutants) | |
| Local name | n-Hexane |
| OEL TWA (mg/m ³) | 70 mg/m ³ |

Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| | |
|--|-----------------------------|
| hexane (110-54-3) | |
| OEL TWA (ppm) | 20 ppm |
| Regulatory reference | Government Notice No. R 904 |
| butane, liquefied, under pressure (106-97-8) | |
| South Africa - Occupational Exposure Limits (Recommended Limits) | |
| Local name | Butane |
| OEL TWA (mg/m ³) | 1430 mg/m ³ |
| OEL TWA (ppm) | 600 ppm |
| OEL STEL (mg/m ³) | 1780 mg/m ³ |
| OEL STEL (ppm) | 750 ppm |
| Regulatory reference | Government Notice. R: 1179 |
| South Africa - Occupational Exposure Limits (Airborne Pollutants) | |
| Local name | n-Butane |
| OEL TWA (mg/m ³) | 1430 mg/m ³ |
| OEL TWA (ppm) | 600 ppm |
| OEL STEL (mg/m ³) | 1780 mg/m ³ |
| OEL STEL (ppm) | 750 ppm |
| Regulatory reference | Government Notice No. R 904 |
| propane (74-98-6) | |
| South Africa - Occupational Exposure Limits (Airborne Pollutants) | |
| Local name | Propane |
| OEL TWA (mg/m ³) | 1800 mg/m ³ |
| OEL TWA (ppm) | 1000 ppm |
| Regulatory reference | Government Notice No. R 904 |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : clear.
Odour : Pineapple coconut.
Odour threshold : No data available
pH : No data available
pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Extremely flammable aerosol.
Vapour pressure : No data available
Vapour pressure at 50 °C : No data available

Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| | |
|---|---|
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Relative density of saturated gas/air mixture | : No data available |
| Density | : No data available |
| Relative gas density | : No data available |
| Solubility | : No data available |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : Pressurised container: May burst if heated. |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |
| Lower explosive limit (LEL) | : No data available |
| Upper explosive limit (UEL) | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|--|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : May be harmful in contact with skin. |
| Acute toxicity (inhalation) | : Not classified |

| | |
|-----------------|---------------------------|
| ATE ZA (dermal) | 3933.787 mg/kg bodyweight |
|-----------------|---------------------------|

| | |
|---------------------------|---|
| hexane (110-54-3) | |
| LD50 oral rat | 16000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral) |
| LD50 dermal rabbit | > 3350 mg/kg bodyweight (Equivalent or similar to OECD 402, 4 h, Rabbit, Male, Read-across, Dermal) |
| LC50 inhalation rat (ppm) | > 5000 ppm (Equivalent or similar to OECD 403, 24 h, Rat, Male, Experimental value, Inhalation (vapours)) |

| | |
|----------------------------|---|
| heptane (142-82-5) | |
| LD50 oral rat | > 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral) |
| LD50 dermal rabbit | > 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal) |
| LC50 inhalation rat (mg/l) | > 29.29 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours)) |

| | |
|-----------------------------|---|
| n-pentane (109-66-0) | |
| LD50 oral rat | > 2000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LC50 inhalation rat (mg/l) | > 20 mg/l air (4 h, Rat, Male / female, Experimental value, Inhalation (vapours)) |

| | |
|---|-----------------------------|
| butane, liquefied, under pressure (106-97-8) | |
| LC50 inhalation rat (mg/l) | 1442.738 - 1443 mg/l 15 MIN |

Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| | |
|---|-------------------|
| butane, liquefied, under pressure (106-97-8) | |
| LC50 inhalation rat (ppm) | 800000 ppm 15 MIN |

| | |
|---------------------------|---|
| propane (74-98-6) | |
| LC50 inhalation rat (ppm) | > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases)) |

| | |
|-----------------------------------|--|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitisation | : May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : May cause harm to breast-fed children. |
| STOT-single exposure | : May cause drowsiness or dizziness. |
| STOT-repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not classified |

| | |
|--|---------|
| Sheen vinyl, plastic & rubber care - Island Coconut | |
| Vaporizer | Aerosol |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|---|
| Ecology - general | : Toxic to aquatic life. Toxic to aquatic life with long lasting effects. |
| Hazardous to the aquatic environment, short-term (acute) | : Toxic to aquatic life. |
| Hazardous to the aquatic environment, long-term (chronic) | : Toxic to aquatic life with long lasting effects. |

| | |
|--------------------------|--|
| hexane (110-54-3) | |
| BCF fish 1 | 501.187 (Other, Pimephales promelas, QSAR) |
| Log Pow | 4 (Experimental value, Equivalent or similar to OECD 107, 20 °C) |
| Log Koc | 3.34 (log Koc, QSAR) |

| | |
|-------------------------------|---|
| heptane (142-82-5) | |
| BCF other aquatic organisms 1 | 552 (BCFBFAF v3.00, Calculated value) |
| Log Pow | 4.66 (Experimental value) |
| Log Koc | 2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |

| | |
|-----------------------------|--|
| n-pentane (109-66-0) | |
| LC50 fish 1 | 4.26 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, GLP) |
| EC50 Daphnia 1 | 2.7 mg/l (Other, 48 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| ErC50 (algae) | 10.7 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Scenedesmus sp., Static system, Fresh water, Experimental value, GLP) |
| BCF fish 1 | 171 (Pimephales promelas, QSAR) |
| Log Pow | 3.45 (Experimental value, Other, 25 °C) |
| Log Koc | 2.9 (log Koc, QSAR) |

| | |
|---|---|
| butane, liquefied, under pressure (106-97-8) | |
| LC50 fish 1 | > 1000 mg/l (96 h, Pimephales promelas, QSAR) |
| EC50 72h algae (1) | 5.3 - 5.5 mg/l (Algae, QSAR) |
| Log Pow | 2.89 (Experimental value) |

| | |
|--------------------------|--|
| propane (74-98-6) | |
| LC50 fish 1 | 24 mg/l (96 h, Pisces, Literature study) |
| LC50 fish 2 | 49.9 mg/l (96 h, Pisces, Fresh water, QSAR) |
| EC50 Daphnia 1 | 7 mg/l (48 h, Daphnia magna, Literature study) |
| BCF fish 1 | 9 - 25 (Pisces, QSAR) |
| Log Pow | 1.09 - 2.8 (Experimental value, 20 °C) |

12.2. Persistence and degradability

| | |
|--|-------------------------------------|
| Sheen vinyl, plastic & rubber care - Island Coconut | |
| Persistence and degradability | No additional information available |

| | |
|-------------------------------|--|
| hexane (110-54-3) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |

Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| | |
|--|--|
| hexane (110-54-3) | |
| ThOD | 3.52 g O ₂ /g substance |
| heptane (142-82-5) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.92 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 0.06 g O ₂ /g substance |
| ThOD | 3.52 g O ₂ /g substance |
| BOD (% of ThOD) | > 0.5 (5 day(s), Literature study) |
| n-pentane (109-66-0) | |
| Persistence and degradability | Readily biodegradable in water. |
| butane, liquefied, under pressure (106-97-8) | |
| Persistence and degradability | Readily biodegradable in water. |
| propane (74-98-6) | |
| Persistence and degradability | Readily biodegradable in water. |
| 12.3. Bioaccumulative potential | |
| Sheen vinyl, plastic & rubber care - Island Coconut | |
| Bioaccumulative potential | No additional information available |
| hexane (110-54-3) | |
| BCF fish 1 | See section 12.1 on ecotoxicology |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | Potential for bioaccumulation (500 ≤ BCF ≤ 5000). |
| heptane (142-82-5) | |
| BCF other aquatic organisms 1 | See section 12.1 on ecotoxicology |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | Potential for bioaccumulation (4 ≥ Log Kow ≤ 5). |
| n-pentane (109-66-0) | |
| BCF fish 1 | See section 12.1 on ecotoxicology |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| butane, liquefied, under pressure (106-97-8) | |
| Log Pow | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| propane (74-98-6) | |
| BCF fish 1 | See section 12.1 on ecotoxicology |
| Log Pow | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| 12.4. Mobility in soil | |
| Sheen vinyl, plastic & rubber care - Island Coconut | |
| Mobility in soil | No additional information available |
| hexane (110-54-3) | |
| Surface tension | 0.018 N/m (25 °C, 1 g/l) |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Ecology - soil | Low potential for mobility in soil. |
| heptane (142-82-5) | |
| Surface tension | 19.66 mN/m (25 °C) |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Ecology - soil | Low potential for adsorption in soil. |
| n-pentane (109-66-0) | |
| Surface tension | 0.013 N/m (20 °C) |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |

Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| | |
|---|---------------------------------------|
| n-pentane (109-66-0) | |
| Ecology - soil | Low potential for adsorption in soil. |
| butane, liquefied, under pressure (106-97-8) | |
| Surface tension | < 0.1 N/m (0 °C) |
| Log Pow | See section 12.1 on ecotoxicology |
| Ecology - soil | Not applicable (gas). |
| propane (74-98-6) | |
| Surface tension | 0.016 N/m (-47 °C) |
| Log Pow | See section 12.1 on ecotoxicology |
| Ecology - soil | Not applicable (gas). |

12.5. Other adverse effects

Ozone : Not classified
 Other adverse effects : No additional information available




SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

| SANS | IMDG | IATA |
|--|---|---|
| 14.1. UN number | | |
| 1950 | 1950 | 1950 |
| 14.2. Proper Shipping Name | | |
| AEROSOLS | AEROSOLS | Aerosols, flammable |
| 14.3. Transport hazard class(es) | | |
| 2.1 | 2.1 | 2.1 |
|  |  |  Not applicable |
| 14.4. Packing group | | |
| Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | |
| Dangerous for the environment : Yes | Dangerous for the environment : No : | Dangerous for the environment : No |
| No supplementary information available | | |

14.6. Special precautions for user

- SANS

Special provisions (SANS) : 63, 190
 Limited quantities (SANS) : See SP277
 Limited quantities (SANS) : See SP277
 Packagings, large packagings and IBCs : P003
 Packing instructions (SANS)
 Packagings, large packagings and IBCs Special : PP17, PP87
 packing instructions (SANS)

- IMDG

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
 Packing instructions (IMDG) : P207, LP200
 Special packing provisions (IMDG) : PP87, L2
 EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
 EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
 Stowage category (IMDG) : None

Sheen vinyl, plastic & rubber care - Island Coconut

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

- IATA

| | |
|--|--------------------|
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

Date of issue : 05/02/2020

Full text of H-statements:

| | |
|------|--|
| H220 | Extremely flammable gas. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H227 | Combustible liquid |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H303 | May be harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H313 | May be harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H362 | May cause harm to breast-fed children. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H401 | Toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

SDS South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.